

MULTI FUNCTIONS PROFESSIONAL FM TRANSCEIVER

ALLPASS

專業對講機

MINI AIR SUPER DEFINITION

超薄機身 · 時尚美觀
鋰電池 · 智慧座充組
CTCSS / DCS 防干擾

LI-ION BATTERY · INTELLIGENT CHARGER · CTCSS/DCS



ALLPASS 專業對講機

MINI AIR SUPER DEFINITION

技術指標

整機部分

頻率範圍	UHF: 400-480MHz
工作溫度	-20°C~+60°C
頻率合成	鎖相環頻率合成
頻率穩定度	±2.5ppm
記憶頻道	16 組頻道
額定電壓	DC 3.7V
天線阻抗	50Ω
工作模式	同頻單工或異頻單工
體積	85mm×38mm×25mm (不含天線)
重量	約150克 (包含電池組)

發射部分

輸出功率	≤5W
調製方式(寬/窄帶)	16KΦF3E, 11KΦF3E
最大頻偏(寬/窄帶)	<5K / <2.5KHz
殘波輻射	<-60dB
發射電流	≤1300mA

接收部分

靈敏度	<0.25μV(12dB SINAD)
靜噪靈敏度	<0.20μV
互調抗干擾	50dB
音訊功率	500mW
接收電流	≤100mA
靜噪待機電流	20mA

*技術指標如因技術需要而有所改動，恕不另行通知

SPECIFICATION

GENERAL		TRANSMIT PART	
Frequency Range	UHF: 400-480MHz	RF Power	≤5W
Operating Temperature	-20°C~+60°C	Modulate Mode [W/N]	16KΦF3E, 11KΦF3E
Frequency Combination	Phase lock frequency synthesize	Max. Freq. Deviation [W/N]	<5K / <2.5KHz
Frequency Stability	±2.5ppm	Remain Wave Radiation	<-60dB
Memory Channel	16 Channels	Transmitting Current	≤1300mA
Working voltage	DC 3.7V	RECEIVE PART	
Antenna Impedance	50Ω	Sensitivity	<0.25μV(12dB SINAD)
Operating Mode	Simplex of co-frequency or alien frequency	Squelch Sensitivity	<0.20μV
Dimension	85mm×38mm×25mm	Intermodulation Antijamming	50dB
Weight	150g (Include Battery Pack)	Audio Power output	500mW
		Receiving Current	≤100mA
		Squelch Standby	20mA

Notice: Saving your presence, no additional notice will be sent if specification changes because of technology-improving.